

UHF Medium Range Reader - DL930
(Single Antenna Inbuilt)

www.RFID-in-China.com

E-mail: info@rfid-in-china.com

Tel : +86-20-86337193

Mob: +86-15817191372



SPECIFICATIONS

ITEM	COMMENT
Support Protocol	ISO18000-6B / ISO18000-6C (EPC Gen2)
Operating Frequency	860MHz ~ 960MHz
Working Mode	FHSS or working mode of fixed frequency pulse transmitting set by software
Transmit Power	20dBm ~ 30 dBm (set by software)

PERFORMANCE

ITEM	COMMENT
Reading Range	4m ~ 8m
Read Speed	The average read time for single card is less than 10ms per 64 bits
Write Distance	2m ~ 4m
Write Speed	8bits less than 30ms
Read Prompt	Buzzer

DATA PORT INTERFACE

ITEM	COMMENT
USB Port	Yes
RS232 Port	Yes
RS485 Port	Yes
Weigand Port	Weigand26/34
Trigger port	Yes
TCP/IP Port (RJ45)	Yes

ELECTRIC PARAMETER

ITEM	COMMENT
Power Supply	DC+9V,4A
Power Consumption	6W

EXTERIOR AND WEIGHT

ITEM	COMMENT
Color	White (can be customized)
Dimension	235mm×235mm×50mm
Weight	1500g

WORKING ENVIRONMENT

ITEM	COMMENT
Operating Temperature	-30° C ~ +70° C

Remark:

- 1. Specifications are subject to change, please pay attention to our latest one.*
- 2. DAILY RFID reserves the right to the final interpretation of the above terms.*